Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-255-2440

	•
Section Quantity:	
1	
Reliability Indicator:	
Not established	
First Flat Length:	
0.406 inches	
Flat Height:	
0.216 inches	
Shaft Diameter:	
0.250 inches	
Shaft Length:	
0.844 inches	
Mounting Bushing Length:	
0.375 inches	
Shaft Style:	
Round, flatted	
Shaft Bearing Type:	
Bearing	
Switch Type:	
Rotary	
Switch Voltage Rating In Volts:	
125.0	
Actuator Type:	
Single shaft	
Switch Operating Position:	
Start of rotation	
Switch Contact Arrangement:	
Single pole, single throw, normally open, both positions mainta	lined
Screw Thread Diameter:	
0.375 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Mounting Method:	
Standard bushing	
Features Provided:	
Switch	
Electrical Resistance Per Section:	
25.000 kilohms single section	
Function Conformity Per Section:	
Single section independent linearity	

Single section independent linearity

NSN 5905-00-255-2440 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent: -20.0 to 20.0 single section Switch Current Type And Rating In Amps: 3.000 ac/dc Standard Taper Curve Per Section: X single section Terminal Type And Quantity: 5 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0