NSN 5905-00-255-5688

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-255-5688 **Section Quantity: Body Style:** Cylindrical studs mounted **Reliability Indicator:** Not established **Body Diameter:** 2.250 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Body Length:** 1.500 inches **Body Inside Diameter:** 0.188 inches **Mounting Hole/stud Circle Diameter:** 1.750 inches **Shaft Style:** Round, hollowed **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Screw Thread Diameter:** 0.164 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:**

Terminal Location: Rear end **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 50.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 324.0 **Power Dissipation Rating Per Section In Watts:** 6.0 free air single section

NSN 5905-00-255-5688

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-2.0 to 2.0 single section
Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0