NSN 5905-00-256-1505

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-256-1505 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.304 inches **Overall Height:** 0.315 inches **Overall Width:** 0.280 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.054 inches **Shaft Length:** 0.120 inches **Body Length:** 1.250 inches **Body Width:** 0.280 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Maximum Running Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Rear end

Mounting Method: Unthreaded hole

Electrical Resistance Per Section:

5.0 kilohms single section

NSN 5905-00-256-1505

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0