## NSN 5905-00-256-6894

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-256-6894 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Pilot Diameter:** 0.7500 inches Pilot Length: 0.6200 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.400 inches **Body Length:** 1.270 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.6200 inches **Shaft Style:** Round, slotted **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 347.0 **Shaft End Play:** 0.00400 inches **Shaft Radial Play:** 0.001 inches **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:** 151.0 2nd section

351.5

**Rotary Actuator Travel In Angular Deg:** 

## NSN 5905-00-256-6894

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fixed Tap Quantity Per Section:
9 1st section
<b>Actuator Travel Control Feature:</b>
Stops
Terminal Type And Quantity:
16 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0