Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-256-6894

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Pilot Diameter:

0.7500 inches

Pilot Length:

0.6200 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0570 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.400 inches

Body Length:

1.270 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.6200 inches

Shaft Style:

Round, slotted

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

347.0

Shaft End Play:

0.00400 inches

Shaft Radial Play:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

151.0 2nd section

Rotary Actuator Travel In Angular Deg:

351.5

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fixed Tap Quantity Per Section:

9 1st section

Actuator Travel Control Feature:

Stops

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0