NSN 5905-00-256-8054

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-256-8054 **Section Quantity: Shaft Diameter:** 0.250 inches **Shaft Length:** 0.250 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:** 1.10 inch-ounces **Maximum Running Torque:** 0.70 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.002 inches **Shaft Radial Play:** 0.002 inches **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 55.000 percent, rated amperes c and better industrial clears **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.30/+0.30 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 3.7 free air single section **Function Conformity Per Section:** Single section independent linearity

-3.0/+3.0 2nd section

Resistance Tolerance Per Section In Percent:

NSN 5905-00-256-8054

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
10 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: