Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-257-6822

Section Quantity:
Reliability Indicator:
Not established
Overall Length:
1.719 inches
Overall Diameter:
3.000 inches
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
310.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
1.00 inch-ounces
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
7.137 kilohms single section
Function Conformity Tolerance Per Section:
-0.33/+0.33 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
20.0 single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-0.33/+0.33 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
3.0 single section



**Special Features:** 

Mtg holes spaced 120 degrees apart on 0.875 in. Radius

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0