NSN 5905-00-257-7488

Section Quantity:

6 solder stud

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-257-7488

1
Reliability Indicator:
Not established
Shaft Diameter:
0.219 inches
Shaft Length:
0.250 inches
Overall Diameter:
2.000 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
1.00 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Screw Thread Diameter:
0.138 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
200.000 ohms single section
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Terminal Type And Quantity:

NSN 5905-00-257-7488

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Damilitarination.

Demilitarization:

No

Fiig:

A002a0