## NSN 5905-00-257-8360

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-257-8360 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.438 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.234 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 15.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.2 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Inorganic cement coating **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

--- Demilitarization:

## NSN 5905-00-257-8360

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0