

NSN 5905-00-257-8486 Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-257-8486 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.063 inches **Body Diameter:** Between 2.422 inches and 2.453 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches Shaft Length: Between 0.859 inches and 0.891 inches **Mounting Bushing Length:** Between 0.359 inches and 0.391 inches **Body Length:** Between 1.578 inches and 1.609 inches **Overall Diameter:** Between 2.578 inches and 2.609 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.512 inches

0.375 inches

Screw Thread Series Designator:

Screw Thread Diameter:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

100.0 ohms single section

Power Dissipation Rating Per Section In Watts:

50.0 free air single section

NSN 5905-00-257-8486

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0