## NSN 5905-00-258-3925

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-258-3925

| Section Quantity:                              |
|--|
| 1  |
| Reliability Indicator:                         |
| Not established                                |
| First Flat Length:                             |
| 0.625 inches                                   |
| Flat Height:                                   |
| 0.216 inches                                   |
| Shaft Diameter:                                |
| 0.250 inches                                   |
| Shaft Length:                                  |
| 2.750 inches                                   |
| Shaft Style:                                   |
| Round, flatted                                 |
| Actuator Type:                                 |
| Single shaft                                   |
| Nonturn Device Location:                       |
| At 3 oclock and at 9 oclock                    |
| Nonturn Device Radius:                         |
| 0.438 inches                                   |
| Screw Thread Diameter:                         |
| 0.375 inches                                   |
| Screw Thread Series Designator:                |
| Unef   |
| Screw Thready Qty Per Inch (tpi):              |
| 32.0   |
| Mounting Method:                               |
| Standard bushing                               |
| Electrical Resistance Per Section:             |
| 50.000 kilohms single section                  |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section                    |
| Resistance Tolerance Per Section In Percent:   |
| -20.0 to 20.0 single section                   |
| Standard Taper Curve Per Section:              |
| A single section                               |
| Special Features:                              |
| Incl. Phenolic insulator in middle of shaft    |
| Terminal Type And Quantity:                    |
| 3 tab, solder lug                              |
| Shelf Life:                                    |
| N/a  |

## NSN 5905-00-258-3925

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A002a0