NSN 5905-00-258-4878

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-258-4878

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.062 inches
Shaft Diameter:
0.250 inches
Shaft Length:
3.000 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.562 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 megohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Posistance Tolerance Per Section In Percent:

A single section

-10.1 to 10.1 single section

Standard Taper Curve Per Section:

NSN 5905-00-258-4878

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0