## NSN 5905-00-258-4879

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-258-4879 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.562 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 3.000 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 0.562 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 12.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing

Electrical Resistance Per Section: 1.0 megohms single section

## NSN 5905-00-258-4879

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

Onch End

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0