## NSN 5905-00-258-6729

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-258-6729

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.266 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 ohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Fixed Tap Quantity Per Section:
1 single section

Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section

## NSN 5905-00-258-6729

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tap Location From Ccw Terminal Per Section In Ohms:	Tap I	Location	From	Ccw	<b>Terminal</b>	Per	<b>Section</b>	In	Ohms:
---	-------	----------	------	-----	-----------------	-----	----------------	----	-------

250.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0