NSN 5905-00-258-7059

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-258-7059

| Section Quantity: |
|---|
| 1 |
| Reliability Indicator: |
| Not established |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.625 inches |
| Shaft Style: |
| Round |
| Switch Type: |
| Rotary |
| Switch Voltage Rating In Volts: |
| 125.0 |
| Actuator Type: |
| Single shaft |
| Switch Contact Arrangement: |
| Single pole, single throw, normally open, both positions maintained |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Method: |
| Standard bushing |
| Features Provided: |
| Switch |
| Electrical Resistance Per Section: |
| 1.1 ohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| Switch Current Type And Rating In Amps: |
| 3.000 ac/dc |
| |
| Standard Taper Curve Per Section: |
| Standard Taper Curve Per Section: A single section |
| |
| A single section |

N/a

NSN 5905-00-258-7059

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A002a0