

View Online at <https://aerobasegroup.com/nsn/5905-00-258-7067>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.250 inches

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.249 inches and 0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.375 inches

Overall Diameter:

1.015 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 6 o'clock

Nonturn Device Radius:

0.359 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

50.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

80.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0