Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-258-7099

# Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

## **Reliability Indicator:**

Not established

### Body Diameter:

0.775 inches

#### Mounting Hole Diameter:

0.136 inches

**Body Length:** 

0.360 inches

Actuator Type:

#### Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

235.0

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

### **Mounting Facility Quantity:**

2

#### Terminal Location:

Rear end

#### Mounting Method:

Unthreaded hole

#### **Features Provided:**

Grounded contact arm

#### **Electrical Resistance Per Section:**

750.000 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

245.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

### **Actuator Travel Control Feature:**

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

# Standard Taper Curve Per Section:

A single section



# Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0