NSN 5905-00-258-9122

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-258-9122

Section Quantity:		
1		
Body Style:		
Cylindrical bushing mounted		
Reliability Indicator:		
Not established		
Overall Length:		
1.312 inches		
Body Diameter:		
1.062 inches		
Shaft Diameter:		
0.125 inches		
Shaft Length:		
0.438 inches		
Mounting Bushing Length:		
0.250 inches		
Body Length:		
0.562 inches		
Shaft Style:		
Round		
Actuator Type:		
Single shaft		
Screw Thread Diameter:		
0.250 inches		
Screw Thread Series Designator:		
Unef		
Screw Thready Qty Per Inch (tpi):		
32.0		
Terminal Location:		
Radially positioned over less than half the circumference		
Mounting Method:		
Locking bushing		
Electrical Resistance Per Section:		
50.0 kilohms single section		
Power Dissipation Rating Per Section In Watts:		
3.0 free air single section		
Resistance Tolerance Per Section In Percent:		
-10.0 to 10.0 single section		
Standard Taper Curve Per Section:		
A single section		
Terminal Type And Quantity:		

2 tab, solder lug

NSN 5905-00-258-9122

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Reference Number	 Differentiating 	Characteristics:
------------------	-------------------------------------	------------------

As differentiated by res and tolerance

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0