NSN 5905-00-259-1955

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-259-1955 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.0750 inches Pilot Length: 0.0620 inches **Overall Length:** 2.906 inches First Flat Length: 0.250 inches Flat Height: 0.231 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0930 inches **Body Diameter:** 2.000 inches **Angle Of Mounting Hole In Deg: Angle Between Centerlines Of Mounting Holes In Deg:** 45.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.593 inches **Body Length:** 2.187 inches **Overall Diameter:** 2.062 inches **Mounting Lip Diameter: Mounting Hole/stud Circle Diameter:**

2.0000 inches **Mounting Lip Depth:** 0.0620 inches 1.250 inches **Shaft Style:** Round, flat, undercut

NSN 5905-00-259-1955

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
1.50 inch-ounces
Maximum Running Torque:
1.00 inch-ounces
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

NSN 5905-00-259-1955

Precision Wire Wound Variable Resistor - Page 3 of 3



Special	Features

Mtg holes 0.188 in. Deep equally spaced on 1.250 in bolt circle

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0