## NSN 5905-00-259-1960

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-259-1960 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 2.187 inches First Flat Length: 0.312 inches Flat Height: 0.188 inches **Undercut Diameter:** 1.812 inches **Undercut Width:** 0.0930 inches **Body Diameter:** 1.875 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.094 inches **Body Length:** 2.062 inches **Overall Diameter:** 1.812 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches

**Shaft Style:** Round, flatted

## NSN 5905-00-259-1960

Precision Wire Wound Variable Resistor - Page 2 of 3



## **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Screw Thread Diameter:** 0.164 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:** 3 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Threaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -2.0/+2.0 ohms single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops

**Tap Location From Ccw Terminal Per Section In Ohms:** 

5000.0 single section

**Function Characteristic Per Section:** 

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

## NSN 5905-00-259-1960

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0