## NSN 5905-00-259-2799

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-2799 **Section Quantity: Reliability Indicator:** Not established First Flat Length: 0.625 inches Flat Height: 0.216 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 250.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5905-00-259-2799

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0