Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-2960

#### Section Quantity:

2

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

### **Terminal Length:**

0.406 inches

#### **Body Diameter:**

1.250 inches

Shaft Diameter:

0.266 inches

Shaft Length:

0.500 inches

#### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

1.250 inches

#### **Overall Diameter:**

1.656 inches

### Shaft Style:

Round, slotted

#### Actuator Type:

Dual concentric

### Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.531 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

40.0 ohms 1st section

# Power Dissipation Rating Per Section In Watts:

2.0 free air all sections



Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0