NSN 5905-00-259-3232

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-3232 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Body Diameter:** 1.812 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 2.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 1.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Fixed Tap Quantity Per Section:** 1 single section

Resistance Tolerance Per Section In Percent:

-1.0 to 1.0 single section

NSN 5905-00-259-3232

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No