NSN 5905-00-259-3738

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-3738

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.594 inches **Shaft Style:** Round, slotted **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 65.0 ohms single section **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

NSN 5905-00-259-3738

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No **Fiig:**

A002a0