## NSN 5905-00-259-3761

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-3761

Out the Out the
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.812 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.594 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 ohms single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

A single section

**Standard Taper Curve Per Section:** 

## NSN 5905-00-259-3761

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0