NSN 5905-00-259-3804

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-3804

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.344 inches
Flat Height:
0.219 inches
Body Diameter:
2.375 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.438 inches
Overall Diameter:
2.688 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
1.250 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:

25.000 ohms single section

NSN 5905-00-259-3804

Precision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts: 40.0 free air single section Resistance Tolerance Per Section In Percent: -15.0/+15.0 single section Special Features: Mtg bracket furnished Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A002a0