NSN 5905-00-259-3920

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-3920

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.109 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.969 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.438 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 kilohms 2nd section
Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Resistance Tolerance Per Section In Percent:

A all sections

-20.0 to 20.0 all sections

Standard Taper Curve Per Section:

NSN 5905-00-259-3920

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0