Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-3938

#### Section Quantity:

2

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.500 inches

#### Body Diameter:

0.938 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

#### Mounting Bushing Length:

## 0.250 inches

**Body Length:** 

0.875 inches

Shaft Style:

Round

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

1.0 megohms 1st section

# Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

# Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 all sections



Standard Taper Curve Per Section:

A all sections

## Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0