NSN 5905-00-259-4557

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-4557 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.250 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.170 inches **Mounting Bushing Length:** 0.170 inches **Body Length:** 1.160 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 14400.0 **Screw Thread Diameter:** 0.216 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 28.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 14400.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

2.5 free air single section

NSN 5905-00-259-4557

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No