NSN 5905-00-259-5086

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-259-5086

-200.0/+200.0 Electrical Resistance: 5.100 kilohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 68.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 250.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.00-4250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating in Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Tost Data Document: Axial terminal each end Tost Data Document: Ostro Basic Soverning drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
8. Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+255.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal sech end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	-200.0/+200.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Avial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No Unit Of Measure:	Electrical Resistance:
-1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	5.100 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 66.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 255.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc., excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure: Demilitarization: No Filg:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04/250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.04-250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	66.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-56.0/+250.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	250.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+250.0
Terminal Type: Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Encapsulated
Reactance Characteristic: Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Noninductive Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter: 0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reactance Characteristic:
0.578 inches Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Noninductive
Body Length: 1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
1.500 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.578 inches
Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
0.250 free air Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.500 inches
Special Features: Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Power Dissipation Rating In Watts:
Terminal type per body style Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Style Designator: Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
Axial terminal each end Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal type per body style
Test Data Document: 18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	18876-8010530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0