NSN 5905-00-259-6262

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-6262

| Section Quantity: |
|--|
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 2.068 inches |
| Body Diameter: |
| Between 1.265 inches and 1.297 inches |
| Shaft Diameter: |
| Between 0.234 inches and 0.266 inches |
| Shaft Length: |
| Between 0.995 inches and 1.000 inches |
| Mounting Bushing Length: |
| Between 0.370 inches and 0.380 inches |
| Body Length: |
| Between 0.578 inches and 0.609 inches |
| Shaft Style: |
| Round |
| Actuator Type: |
| Single shaft |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 90.0 kilohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.5 free air single section |
| Fixed Tap Quantity Per Section: |
| 3 single section |
| Tap Location Tolerance Per Section: |
| -15.0 to 15.0 ohms single section |
| Resistance Tolerance Per Section In Percent: |
| -15.0 to 15.0 single section |
| |

NSN 5905-00-259-6262

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tap Location From Ccw Terminal Per Section In Ohms:

22500.0 single section and 45000.0 single section and 67500.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0