NSN 5905-00-259-6262

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-6262

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.068 inches
Body Diameter:
Between 1.265 inches and 1.297 inches
Shaft Diameter:
Between 0.234 inches and 0.266 inches
Shaft Length:
Between 0.995 inches and 1.000 inches
Mounting Bushing Length:
Between 0.370 inches and 0.380 inches
Body Length:
Between 0.578 inches and 0.609 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
90.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Fixed Tap Quantity Per Section:
3 single section
Tap Location Tolerance Per Section:
-15.0 to 15.0 ohms single section
Resistance Tolerance Per Section In Percent:
-15.0 to 15.0 single section

NSN 5905-00-259-6262

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tap Location From Ccw Terminal Per Section In Ohms:

22500.0 single section and 45000.0 single section and 67500.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0