## NSN 5905-00-259-6285

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-6285 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.344 inches Flat Height: 0.219 inches **Body Diameter: 2.312 inches Shaft Diameter:** 0.250 inches **Shaft Length:** 0.781 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 3.500 inches **Overall Diameter:** 3.000 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 

8.0 ohms all sections

**Power Dissipation Rating Per Section In Watts:** 

50.0 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 all sections

## NSN 5905-00-259-6285

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0