NSN 5905-00-259-7712

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-259-7712 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.500 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.625 inches **Overall Diameter:** 1.812 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 292.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 194.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches Mechanical Backlash In Deg Angular Rotation: 1.5 **Screw Thread Diameter:**

Screw Thread Series Designator: Unef

0.375 inches

NSN 5905-00-259-7712

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



32.0	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
_ocking bushing	
Cubic Measure:	
0.656 cubic inches	
Electrical Resistance Per Section:	
25.000 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
312.0	
Resistance Tempurature Characteristic Range Per Section In Percent:	
+0.0 to 7.0 -55 degrees celsius single section and +0.0 to 3.5 -25 degrees celsius single section and -2.5 to 2.5 85 degre	es celsius single
section and +0.0 to 5.5 120 degrees celsius single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
120.0 single section	
Power Dissipation Rating Per Section In Watts:	
2.25 free air single section	
Resistance Tolerance Per Section In Percent:	
10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
4002a0	