

View Online at <https://aerobasegroup.com/nsn/5905-00-259-9750>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.375 inches

Flat Height:

0.218 inches

Body Diameter:

1.094 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.515 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 oclock or at 6 oclock or at 9 oclock or at 12 oclock

Nonturn Device Radius:

0.500 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

2.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

100.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Has 0.188 in hole drilled through shaft 0.375 in from end parallel to flatted surface

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0