NSN 5905-00-261-7243

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-261-7243 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.655 inches **Body Diameter:** 0.937 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.562 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.828 inches **Overall Diameter:** 1.258 inches **Shaft Style:** Round Switch Type: Push-pull **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Switch Operating Position:** Any position of rotation travel **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

NSN 5905-00-261-7243

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 heat sink single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Switch Current Type And Rating In Amps:
1.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0