Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-262-0557

Section	Quantity:	
1		
Reliabili	ity Indicator:	
Not esta	blished	
Shaft Di	iameter:	
0.060 inc	ches	
Shaft St	yle:	
Round,	slotted	
Actuato	r Type:	
Single sh	haft	
Effective	e Electrical Rotation In Deg Angular Rotation:	
9000.0		
Maximu	m Starting Torque:	
5.00 inch	h-ounces	
Electrica	al Resistance Per Section:	
1.0 kiloh	ms single section	
Rotary A	Actuator Travel In Angular Deg:	
9000.0		
Ambient	t Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
175.0 sir	ngle section	
Tempura	ature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-70.0 to	70.0 single section	
Power D	Dissipation Rating Per Section In Watts:	
1.0 free a	air single section	
Resistar	nce Tolerance Per Section In Percent:	
-5.0 to 5.	.0 single section	
Actuato	r Travel Control Feature:	
Clutch		
Ambient	t Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 sing	gle section	
Standar	d Taper Curve Per Section:	
A single	section	
Test Dat	ta Document:	
07690-42	29571 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc).;
excludes	s any specification, standard or other document that may be referenced in a basic governing drawing)	
Termina	al Type And Quantity:	
3 pin		
Shelf Lif	fe:	
N/a		
Unit Of I	Measure:	
Demilita	arization:	
No		

NSN 5905-00-262-0557

Nonprecision Wire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

