Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-263-0574

Section	Quantity:

1

- First Flat Length:
- 0.625 inches
- Flat Height:
- 0.216 inches
- Shaft Diameter:
- 0.250 inches
- Shaft Length:
- 1.000 inches
- Shaft Style:
- Round, flatted
- Actuator Type:
- Single shaft
- Nonturn Device Location:
- At 3 oclock
- Nonturn Device Radius:
- 0.531 inches
- Screw Thread Diameter:
- 0.375 inches
- Screw Thread Series Designator:
- Unef
- Screw Thready Qty Per Inch (tpi):
- 32.0
- **Mounting Method:**
- Standard bushing
- **Electrical Resistance Per Section:**
- 1.000 megohms single section
- **Power Dissipation Rating Per Section In Watts:**
- 0.5 free air single section
- **Resistance Tolerance Per Section In Percent:**
- -20.0 to 20.0 single section
- Standard Taper Curve Per Section:
- K single section
- Terminal Type And Quantity:
- 3 tab, solder lug
- Shelf Life:
- N/a
- Unit Of Measure:
- ---
- Demilitarization:
- No

NSN 5905-00-263-0574

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

