Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-264-7753

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.062 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.375 inches

## Mounting Bushing Length:

0.375 inches

#### Body Length:

# 0.438 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### Mounting Method:

Standard bushing

#### **Features Provided:**

Grounded contact arm

#### **Electrical Resistance Per Section:**

1.0 kilohms single section

## **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

## Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

3 tab, solder lug

# NSN 5905-00-264-7753

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0