NSN 5905-00-264-7817

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-264-7817 **Section Quantity:** 3 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.687 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.812 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:**

1.000 megohms all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

NSN 5905-00-264-7817

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



5	esistance	Tolerance	Per Section	In Percent
۲	esistance	i olerance	rei Section	ın Fercent.

-10.0 to 10.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0