Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-264-9286

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.562 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

### Mounting Bushing Length:

0.375 inches

#### Body Length:

1.250 inches

### Shaft Style:

Round

### Actuator Type:

Single shaft

## Nonturn Device Location:

At 3 oclock or at 6 oclock or at 9 oclock or at 12 oclock

### **Nonturn Device Radius:**

0.500 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

10.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

25.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Standard Taper Curve Per Section:

A single section



Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0