NSN 5905-00-266-0943

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-266-0943
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.812 inches
Body Diameter:
1.880 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.750 inches
Overall Diameter:
1.880 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
40.00 inch-ounces
Maximum Stop Torque:
240.00 inch-ounces
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
Between 0.485 inches and 0.515 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end

Mounting Method:Standard bushing

NSN 5905-00-266-0943

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
250.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 280.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
12.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: