Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-267-9274

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

0.907 inches

#### **Body Diameter:**

1.625 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.344 inches

#### Mounting Bushing Length:

## 0.375 inches

**Body Length:** 

0.563 inches

Shaft Style:

Round, slotted

## Shaft Bearing Type:

Bearing

#### Actuator Type:

Single shaft

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

25.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

4.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### Standard Taper Curve Per Section:

A single section



# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0