## NSN 5905-00-270-1941

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-270-1941 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.719 inches **Body Diameter:** 0.562 inches **Body Length:** 0.453 inches **Overall Diameter:** 0.562 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 290.0 **Fragility Factor:** Moderately delicate **Screw Thread Diameter:** 0.086 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 56.0 **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Threaded stud **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 2.2 kilohms single section **Rotary Actuator Travel In Angular Deg:** 290.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-500.0 to 500.0 single section

## NSN 5905-00-270-1941

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Case turns, not shaft
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0