Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-270-2006

Section Qua	antity:
1	
Body Style:	
Cylindrical	
Reliability li	ndicator:
Not establish	ned
Body Diame	eter:
0.785 inches	
Body Lengt	h:
0.422 inches	
Actuator Ty	pe:
Flush drive v	vith slot-hole
Effective El	ectrical Rotation In Deg Angular Rotation:
240.0	
Terminal Lo	cation:
Rear end	
Mounting M	ethod:
Tab	
Features Pr	ovided:
Grounded co	ontact arm
Electrical R	esistance Per Section:
15.0 ohms s	ingle section
Rotary Actu	ator Travel In Angular Deg:
240.0	
Ambient Te	mpurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single	section
Power Diss	pation Rating Per Section In Watts:
2.0 heat sink	single section
Resistance	Tolerance Per Section In Percent:
-20.0 to 20.0	single section
Actuator Tr	avel Control Feature:
Stops	
Tempuratur	e Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0	single section
Ambient Te	mpurature In Deg Celsius Per Section At Full Rated Power:
55.0 single s	ection
Standard Ta	per Curve Per Section:
A single sec	ion
Terminal Ty	pe And Quantity:
2 tab, solde	r lug
Shelf Life:	
N/a	

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0