NSN 5905-00-273-9642

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-273-9642

Electrical Resistance: 7.500 kilohms Resistance Tolerance In Percent: 4.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air
7.500 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: 1.1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.001 Body Diameter: 1.125 inches Rody Length: 1.0375 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Method: 175.0/+175.0 Tempurature Method: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/+175.0 Tempurature Range Of
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Body Diameter: 10.125 inches Body Length: 10.375 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
D.001 Body Diameter: D.125 inches Body Length: D.375 inches Power Dissipation Rating In Watts:
Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts:
D.125 inches Body Length: D.375 inches Power Dissipation Rating In Watts:
Body Length: 0.375 inches Power Dissipation Rating In Watts:
0.375 inches Power Dissipation Rating In Watts:
Power Dissipation Rating In Watts:
).125 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0