Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2002

| Section Quantity: | |
|--|--|
| 1 | |
| Reliability Indicator: | |
| Not established | |
| First Flat Length: | |
| 0.344 inches | |
| Body Diameter: | |
| 1.562 inches | |
| Shaft Diameter: | |
| 0.250 inches | |
| Shaft Length: | |
| 0.875 inches | |
| Mounting Bushing Length: | |
| 0.375 inches | |
| Body Length: | |
| 1.375 inches | |
| Shaft Style: | |
| Round, flatted | |
| Actuator Type: | |
| Single shaft | |
| Nonturn Device Location: | |
| At 9 oclock | |
| Nonturn Device Radius: | |
| 0.500 inches | |
| Screw Thread Diameter: | |
| 0.375 inches | |
| Screw Thread Series Designator: | |
| Unef | |
| Screw Thready Qty Per Inch (tpi): | |
| 32.0 | |
| Mounting Method: | |
| Standard bushing | |
| Electrical Resistance Per Section: | |
| 125.000 ohms single section | |
| Power Dissipation Rating Per Section In Watts: | |
| 25.0 free air single section | |
| Resistance Tolerance Per Section In Percent: | |
| -10.0 to 10.0 single section | |
| Standard Taper Curve Per Section: | |
| A single section | |
| Terminal Type And Quantity: | |
| | |

3 tab, solder lug

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0