## NSN 5905-00-279-2003

**Section Quantity:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2003

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.344 inches
Flat Height:
0.219 inches
Body Diameter:
2.312 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock or at 6 oclock or at 9 oclock or at 12 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.0 ohms single section
Power Dissipation Rating Per Section In Watts:
50.0 free air single section

## NSN 5905-00-279-2003

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Standard Taper Curve Per Section:** 

J single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0