NSN 5905-00-279-2010

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2010

Section Quantity:
1
Body Style:
Cylindrical hole/slot mounted
Reliability Indicator:
Not established
Overall Length:
4.375 inches
First Flat Length:
1.562 inches
Flat Height:
0.344 inches
Body Diameter:
6.000 inches
Shaft Diameter:
0.375 inches
Shaft Length:
2.000 inches
Body Length:
2.375 inches
Mounting Hole/stud Circle Diameter:
2.375 inches
Shaft Style:
Round, flatted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Distance Between Mounting Hole Centers:
2.375 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:

Threaded hole

NSN 5905-00-279-2010

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
300.000 ohms single section
Power Dissipation Rating Per Section In Watts:
300.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A002a0