## NSN 5905-00-279-2015

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-279-2015

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 1.594 inches and 1.656 inches
First Flat Length:
0.344 inches
Flat Height:
0.219 inches
Body Diameter:
3.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 0.844 inches and 0.906 inches
Mounting Bushing Length:
0.469 inches
Body Length:
1.750 inches
Shaft Style:
Round, flatted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.000 ohms single section

## NSN 5905-00-279-2015

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Power Dissipation Rating Per Section In Watts: 100.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A002a0